



Concrete Coatings

EZ-GLO

WATER BASED ACRYLIC POLISH LEAVES A SMOOTH GLOSSY FINISH

EZ-GLO IS A DETERGENT RESISTANT WATER BASED ACRYLIC FLOOR POLISH. EZ-GLO MAY BE USED ON ALL TYPES OF SEALED CONCRETE FLOORS AS WELL AS SEALED WOOD AND COMPOSITION FLOORS.

PRODUCT HIGHLIGHTS

- EZ-Glo produces a beautiful, high gloss, wet look shine upon drying, without buffing.
- **Highly detergent resistant:** EZ-Glo is not harmed by repeated scrubbing with a neutral detergent, or damp mopping between buffings.
- **Restore worn areas by re-coating with EZ-Glo:** Just damp mop, apply and let dry. Spray Buffing will blend in the re-coated area.
- **Highly slip resistant:** EZ-Glo meets the ASTM D-2407 requirement for slip resistance.
- **Economical:** One gallon of EZ-Glo covers over 1200 sq. ft. per coat, and lasts for months without re-coating.
- Simple Spray Buffing maintenance keeps the clean, bright polished look for months, and the acrylic polymers do not ever yellow. Remove old polish thoroughly by scrubbing with CitraPro. Rinse floor well and let dry completely.

USES

EZ-Glo is used to maintain floors in a brilliant polished condition with minimal labor. All types of sealed concrete floors as well as sealed wood and composition floors will improve their appearance and decrease maintenance costs with the use of EZ-Glo.

QUICK LOOK:

Type : Super acrylic floor polish

Toxicity: Harmful if swallowed

VOC's: None

Flammability: Non-flammable

Composition: Acrylic polymer emulsion, ethylene copolymers, proprietary additives and quality control agents

Color: Colorless, non-yellowing

Odor: Very mild

Coverage: 1000 Sq. Ft. per gallon

**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

FOR MORE INFORMATION,
PLEASE SEE SDS.





EZ-GLO

HOW TO USE:

Remove old polish or wax thoroughly using CitraPro. Thoroughly rinse floor and allow to dry completely. Spread EZ-Glo evenly over entire floor with a Lambs Wool Applicator, or clean yarn mop. Allow to dry completely, usually 25–30 minutes. Always apply EZ-Glo in thin coats. Allow to dry 24 hours before heavy traffic.

Maintenance: Occasional damp mopping with a neutral detergent, such as EZ-Clean, will maintain the smooth glossy surface.

Heavy Traffic Areas: Clean with a neutral detergent, such as EZ Clean. Rinse and damp mop. Let floor dry thoroughly. Apply 1 thin coat of EZ-Glo.

Stripping: CitraPro will easily strip EZ-Glo. As many as 10 coats of EZ-Glo may be applied without the need for stripping. EZ-Glo will not yellow.

Note: *A test area is recommended for all applications.*

PRECAUTIONARY STATEMENT:

Wash hands after handling. Do not eat, drink, or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Dispose of contents/container according to local, state and federal regulations.

FIRST AID:

IF INGESTED: Drink two glasses of water. Get Immediate Medical Help.

IF IN EYES: Flush thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

IF ON SKIN: Wash thoroughly with soap and water.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053