



Concrete Coatings

MICRO TOPPING

SINGLE COMPONENT CEMENTICIOUS OVERLAY

MICRO TOPPING IS A CEMENTBASED, POLYMER MODIFIED DECORATIVE CONCRETETOPPING MATERIAL. SINGLE COMPONENTMICRO TOPPING IS A THINLY APPLIED TOPPING THAT CLOSELY RESEMBLES THE LOOK OF NATURALCONCRETE.

PRODUCT HIGHLIGHTS

- High bond, flexural and compressive strength. Consistant and evenly textured finish.
- Can be integrally colored with EZChem EZ Color Paks.
- Can be stained with EZChem Enviro Stain or Earthtone Stain for a wide array of decorative finishes.
- Can be sealed with EZChem Clear Acrylic Sealer or Colored Acrylic Sealer for a consistently colored and durable surface.
- **Packaged in 40lb bags**

USES

Resurfacing concrete that is worn, pitted or spalled.

Can be used over existing concrete surfaces including decks, patios, sidewalks, driveways and/or any other structurally sound concrete surfaces.

Can be used on vertical concrete surfaces.

QUICK LOOK:

Type :

Toxicity:

VOC's: Zero

Flammability: Non-flammable

Composition:

Odor: N/A

Coverage: 200 - 300 sqft. per bag

**Coverage rates may vary depending on porosity, texture, application method and prior sealer application. Excess buildup should be avoided.*

Application Temperature:

Cured:

FOR MORE INFORMATION,
PLEASE SEE SDS.



Manufactured In The USA By



**Product warranty for one year from date of manufacture*

For more information on EZChem and all products manufactured by EZChem please visit our website: www.ezchemusa.com



Concrete Coatings

MICRO TOPPING

SURFACE PREPERATION:

The surface must be clean and free of any dirt or debris and properly prepped. Just prior to applying Micro Topping, the substrate must be primed with Bond It primer. Do not allow Bond It primer to dry completely. Micro Topping must be applied over wet Bond It.

HOW TO USE:

One 40 pound bag of Micro Topping will require approximately 5 to 7 quarts of water. For best results use a 1/2 inch drill with a Jiffy type mixing paddle. Add the measured water to a clean 5 - gallon pail. Add one EZ Color Pak pigment pack to your measured water and mix in. With the mixer running, slowly add the Micro Topping powder, mixing until a lump free consistency is obtained. Allow the mixed material to set, or slake for approximately 5 minutes and then re-mix prior to placement. Mix only the amount of material that can be placed within 30 minutes of mixing. Keep bagged material and mixed material out of direct sunlight for added work time. Use cold water when mixing for added working time. In cooler conditions, use warm water when mixing. Consult product technical data sheet for surface preparation and installation.

PRECAUTIONARY STATEMENT:

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash hands thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Take off contaminated clothing and wash before reuse. Store in a well-ventilated place. Keep container tightly closed. Store locked up. Dispose of contents/container to approved waste disposal site.

FIRST AID:

INHALATION: Move to fresh air to avoid nuisance symptoms.

SKIN CONTACT: Wash affected area thoroughly with soap and water. Rinse well. If irritation develops Get Medical Help.

EYE CONTACT: Rinse thoroughly with water for 15 minutes, lifting both eyelids. If irritation persists, Get Medical Help.

INGESTION: Rinse mouth with water. Drink 2 glasses of water to dilute. Do not induce vomiting. Get Immediate Medical Help. Never give anything by mouth to an unconscious person.

IN CASE OF FIRE:

This product is not flammable.

FOR EMERGENCY HELP

24 Hours a Day contact:

INFOTRAC at 1-800-535-5053